

Rittal – The System.

Faster – better – everywhere.



SK 3323.107 Fan-and-filter units

State: 5/8/2023 (Source: rittal.com/in-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SK 3323.107 - Fan-and-filter units

Features

Model No.	SK 3323.107
Colour	RAL 7035
Supply includes	Complete unit ready to install, including filter mat
Rated current max.	At 50 Hz: 12 mA At 60 Hz: 11 mA
Mounting cut-out	Cut-out width: 177 mm Cut-out height: 177 mm
At 60 Hz	11 mA
Note	For energy-efficient operation of the fan-and-filter units, we recommend using the enclosure internal thermostat, the speed control or the digital enclosure internal temperature display and thermostat
with chopped-fibre filter and additional fine filter mat	Up to IP 55 is achieved in conjunction with additional fine filter mat
Dimensions	Width: 204 mm Height: 204 mm
IP protection category to IEC 60529	IP 54 Up to IP 55 is achieved in conjunction with additional fine filter mat IP 56
Storage temperature range	-30 °C...70 °C
Power consumption Pel	At 50 Hz: 19 W At 60 Hz: 18 W
Packs of	1 pc(s).
EAN	4028177165410
ETIM 7.0	EC000320