



اینورتر یاسکاوا

CIMR-AC4A0044FAA GBR

YASKAWA

۰۲۱ ۶۶۷۵۶۲۳۱



www.alindas.com



خیابان سرهنگ سخایی ساختمان 44 طبقه سوم واحد 7





CIMR-AC4A0044FAA GBR

اینورتر یاسکاوا

سه فاز



INPUT POWER SUPPLY 400 V	RATED OUTPUT CURRENT (HD) 39 A	RATED OUTPUT CURRENT (ND) 44 A	OVERLOAD TOLERANCE (ND) 120 % for 60 s
OVERLOAD TOLERANCE (HD) 150 % for 60 s	MAX. APPLICABLE MOTOR POWER (HD) 18.5 kW	MAX. APPLICABLE MOTOR POWER (ND) 22 kW	INPUT POWER PHASES 3-phase
MOTOR TYPE Permanent magnet motor, Induction motor	STANDARDS COMPLIANCE cUL, CE, RoHS, UL, UKCA	AMBIENT TEMPERATURE (MIN) -10 °C	AMBIENT TEMPERATURE (MAX) 40 °C
AMBIENT TEMPERATURE (MAX) WITH DERATING 50 °C	MAX. HUMIDITY (NON-CONDENSING) 95 %	MAX. ALTITUDE (WITHOUT DERATING) 1000 m	MAX. ALTITUDE (WITH DERATING) 3000 m
HEIGHT 350 mm	WIDTH 220 mm	DEPTH 197 mm	WEIGHT 8.3 kg
COOLING METHOD Air cooling, Coldplate	ENCLOSURE IP20	ENVIRONMENTAL SPECIFICATIONS Standard	ANALOG INPUT 3
ANALOG OUTPUT 2	DIGITAL INPUT 8	DIGITAL OUTPUT 4	SAFETY LEVEL SIL2
PERFORMANCE LEVEL PL d	TORQUE CONTROL Standard	BRAKING TRANSISTOR External	MOTOR THERMAL PROTECTION Standard
MAX OUTPUT FREQUENCY 400 Hz			

