



اینورتر یاسکاوا

CIMR-AC4A0088AAA GBR

YASKAWA

۰۲۱ ۶۶۷۵۶۲۳۱



www.alindas.com



خیابان سرهنگ سخایی ساختمان 44 طبقه سوم واحد 7





CIMR-AC4A0088AAA GBR

اینورتر یاسکاوا

سه فاز



INPUT POWER SUPPLY
400 V

OVERLOAD TOLERANCE (HD)
150 % for 60 s

MOTOR TYPE
Permanent magnet motor,
Induction motor

**AMBIENT TEMPERATURE (MAX)
WITH DERATING**
50 °C

HEIGHT
510 mm

COOLING METHOD
Air cooling, Coldplate

ANALOG OUTPUT
2

PERFORMANCE LEVEL
PL d

MAX OUTPUT FREQUENCY
400 Hz

RATED OUTPUT CURRENT (HD)
75 A

**MAX. APPLICABLE MOTOR POWER
(HD)**
37 kW

STANDARDS COMPLIANCE
cUL, CE, RoHS, UL, UKCA

**MAX. HUMIDITY (NON-
CONDENSING)**
95 %

WIDTH
325 mm

ENCLOSURE
IP00

DIGITAL INPUT
8

TORQUE CONTROL
Standard

RATED OUTPUT CURRENT (ND)
88 A

**MAX. APPLICABLE MOTOR POWER
(ND)**
45 kW

AMBIENT TEMPERATURE (MIN)
-10 °C

**MAX. ALTITUDE (WITHOUT
DERATING)**
1000 m

DEPTH
258 mm

ENVIRONMENTAL SPECIFICATIONS
Standard

DIGITAL OUTPUT
4

BRAKING TRANSISTOR
External

OVERLOAD TOLERANCE (ND)
120 % for 60 s

INPUT POWER PHASES
3-phase

AMBIENT TEMPERATURE (MAX)
40 °C

MAX. ALTITUDE (WITH DERATING)
3000 m

WEIGHT
36 kg

ANALOG INPUT
3

SAFETY LEVEL
SIL2

MOTOR THERMAL PROTECTION
Standard

