



اینورتر یاسکاوا

CIMR-AC4A0165AAA GBR

YASKAWA

۰۲۱ ۶۶۷۵۶۲۳۱



www.alindas.com



خیابان سرهنگ سخایی ساختمان 44 طبقه سوم واحد 7





CIMR-AC4A0165AAA GBR

اینورتر یاسکاوا

سه فاز



INPUT POWER SUPPLY

400 V

RATED OUTPUT CURRENT (HD)

150 A

RATED OUTPUT CURRENT (ND)

165 A

OVERLOAD TOLERANCE (ND)

120 % for 60 s

OVERLOAD TOLERANCE (HD)

150 % for 60 s

MAX. APPLICABLE MOTOR POWER (HD)

75 kW

MAX. APPLICABLE MOTOR POWER (ND)

90 kW

INPUT POWER PHASES

3-phase

MOTOR TYPE

Permanent magnet motor,
Induction motor

STANDARDS COMPLIANCE

cUL, CE, RoHS, UL, UKCA

AMBIENT TEMPERATURE (MIN)

-10 °C

AMBIENT TEMPERATURE (MAX)

40 °C

AMBIENT TEMPERATURE (MAX) WITH DERATING

50 °C

MAX. HUMIDITY (NON-CONDENSING)

95 %

MAX. ALTITUDE (WITHOUT DERATING)

1000 m

MAX. ALTITUDE (WITH DERATING)

3000 m

HEIGHT

510 mm

WIDTH

325 mm

DEPTH

283 mm

WEIGHT

42 kg

COOLING METHOD

Air cooling, Coldplate

ENCLOSURE

IP00

ENVIRONMENTAL SPECIFICATIONS

Standard

ANALOG INPUT

3

ANALOG OUTPUT

2

DIGITAL INPUT

8

DIGITAL OUTPUT

4

SAFETY LEVEL

SIL2

PERFORMANCE LEVEL

PL d

TORQUE CONTROL

Standard

BRAKING TRANSISTOR

External

MOTOR THERMAL PROTECTION

Standard

MAX OUTPUT FREQUENCY

400 Hz

