



# اینورتر یاسکاوا

CIMR-AC4A0250AAA GBR

# YASKAWA

۰۲۱ ۶۶۷۵۶۲۳۱



[www.alindas.com](http://www.alindas.com)



خیابان سرهنگ سخایی ساختمان 44 طبقه سوم واحد 7





CIMR-AC4A0250AAA GBR

# اینورتر یاسکاوا

سه فاز



<b>INPUT POWER SUPPLY</b> 400 V	<b>RATED OUTPUT CURRENT (HD)</b> 216 A	<b>RATED OUTPUT CURRENT (ND)</b> 250 A	<b>OVERLOAD TOLERANCE (ND)</b> 120 % for 60 s
<b>OVERLOAD TOLERANCE (HD)</b> 150 % for 60 s	<b>MAX. APPLICABLE MOTOR POWER (HD)</b> 110 kW	<b>MAX. APPLICABLE MOTOR POWER (ND)</b> 132 kW	<b>INPUT POWER PHASES</b> 3-phase
<b>MOTOR TYPE</b> Permanent magnet motor, Induction motor	<b>STANDARDS COMPLIANCE</b> cUL, CE, RoHS, UL, UKCA	<b>AMBIENT TEMPERATURE (MIN)</b> -10 °C	<b>AMBIENT TEMPERATURE (MAX)</b> 40 °C
<b>AMBIENT TEMPERATURE (MAX) WITH DERATING</b> 50 °C	<b>MAX. HUMIDITY (NON-CONDENSING)</b> 95 %	<b>MAX. ALTITUDE (WITHOUT DERATING)</b> 1000 m	<b>MAX. ALTITUDE (WITH DERATING)</b> 3000 m
<b>HEIGHT</b> 800 mm	<b>WIDTH</b> 500 mm	<b>DEPTH</b> 350 mm	<b>WEIGHT</b> 96 kg
<b>COOLING METHOD</b> Air cooling, Coldplate	<b>ENCLOSURE</b> IP00	<b>ENVIRONMENTAL SPECIFICATIONS</b> Standard	<b>ANALOG INPUT</b> 3
<b>ANALOG OUTPUT</b> 2	<b>DIGITAL INPUT</b> 8	<b>DIGITAL OUTPUT</b> 4	<b>SAFETY LEVEL</b> SIL2
<b>PERFORMANCE LEVEL</b> PL d	<b>TORQUE CONTROL</b> Standard	<b>BRAKING TRANSISTOR</b> External	<b>MOTOR THERMAL PROTECTION</b> Standard
<b>MAX OUTPUT FREQUENCY</b> 400 Hz			

