



اینورتر یاسکاوا

CMIR-VC4A0007BAA - VZA42P2BAA

YASKAWA

۰۲۱ ۶۶۷۵۶۲۳۱



www.alindas.com



خیابان سرهنگ سخایی ساختمان 44 طبقه سوم واحد 7





CMIR-VC4A0007BAA - VZA42P2BAA

اینورتر یاسکوا

سه فاز



INPUT POWER SUPPLY 400 V	RATED OUTPUT CURRENT (HD) 5.5 A	RATED OUTPUT CURRENT (ND) 6.9 A	OVERLOAD TOLERANCE (ND) 120 % for 60 s
OVERLOAD TOLERANCE (HD) 150 % for 60 s	MAX. APPLICABLE MOTOR POWER (HD) 2.2 kW	MAX. APPLICABLE MOTOR POWER (ND) 3 kW	INPUT POWER PHASES 3-phase
MOTOR TYPE Permanent magnet motor, Induction motor	STANDARDS COMPLIANCE cUL, CE, RoHS, UL, UKCA	AMBIENT TEMPERATURE (MIN) -10 °C	AMBIENT TEMPERATURE (MAX) 50 °C
MAX. HUMIDITY (NON-CONDENSING) 95 %	MAX. ALTITUDE (WITHOUT DERATING) 1000 m	MAX. ALTITUDE (WITH DERATING) 3000 m	HEIGHT 128 mm
WIDTH 108 mm	DEPTH 154 mm	WEIGHT 1.7 kg	COOLING METHOD Coldplate, Air cooling
ENCLOSURE IP20/UL Open Type	ENVIRONMENTAL SPECIFICATIONS Standard	ANALOG INPUT 2	ANALOG OUTPUT 1
DIGITAL INPUT 6	DIGITAL OUTPUT 3	SAFETY LEVEL SIL2	PERFORMANCE LEVEL PL d
TORQUE CONTROL Not available	BRAKING TRANSISTOR External	MOTOR THERMAL PROTECTION Standard	MAX OUTPUT FREQUENCY 400 Hz

