



# اینورتر یاسکاوا

VZA40P7BAA\_CIMR-VC4A0004BAA

YASKAWA

۰۲۱ ۶۶۷۵۶۲۳۱



www.alindas.com



خیابان سرهنگ سخایی ساختمان 44 طبقه سوم واحد 7





VZA40P7BAA\_CIMR-VC4A0004BAA

# اینورتر یاسکوا

سه فاز



<b>INPUT POWER SUPPLY</b> 400 V	<b>RATED OUTPUT CURRENT (HD)</b> 3.4 A	<b>RATED OUTPUT CURRENT (ND)</b> 4.1 A	<b>OVERLOAD TOLERANCE (ND)</b> 120 % for 60 s
<b>OVERLOAD TOLERANCE (HD)</b> 150 % for 60 s	<b>MAX. APPLICABLE MOTOR POWER (HD)</b> 1.1 kW	<b>MAX. APPLICABLE MOTOR POWER (ND)</b> 1.5 kW	<b>INPUT POWER PHASES</b> 3-phase
<b>MOTOR TYPE</b> Permanent magnet motor, Induction motor	<b>STANDARDS COMPLIANCE</b> cUL, CE, RoHS, UL, UKCA	<b>AMBIENT TEMPERATURE (MIN)</b> -10 °C	<b>AMBIENT TEMPERATURE (MAX)</b> 50 °C
<b>MAX. HUMIDITY (NON-CONDENSING)</b> 95 %	<b>MAX. ALTITUDE (WITHOUT DERATING)</b> 1000 m	<b>MAX. ALTITUDE (WITH DERATING)</b> 3000 m	<b>HEIGHT</b> 128 mm
<b>WIDTH</b> 108 mm	<b>DEPTH</b> 137.5 mm	<b>WEIGHT</b> 1.7 kg	<b>COOLING METHOD</b> Coldplate, Air cooling
<b>ENCLOSURE</b> IP20/UL Open Type	<b>ENVIRONMENTAL SPECIFICATIONS</b> Standard	<b>ANALOG INPUT</b> 2	<b>ANALOG OUTPUT</b> 1
<b>DIGITAL INPUT</b> 6	<b>DIGITAL OUTPUT</b> 3	<b>SAFETY LEVEL</b> SIL2	<b>PERFORMANCE LEVEL</b> PL d
<b>TORQUE CONTROL</b> Not available	<b>BRAKING TRANSISTOR</b> External	<b>MOTOR THERMAL PROTECTION</b> Standard	<b>MAX OUTPUT FREQUENCY</b> 400 Hz

