



# پی ال سی امرن (PLC) مدل CP1E-N30S1DR-A



# CP1E-N30S1DR-A

پی ال سی امرن (PLC)  
ولتاژ تغذیه 240-120 ولت و خروجی رله



|                                      |  |
|--------------------------------------|--|
| Supply voltage type                  | AC   |
| Number of digital inputs             | 18   |
| Input type                           | PNP/NPN  |
| Number of digital outputs            | 12   |
| Output type                          | Relay  |
| Program capacity                     | 8 K steps  |
| Data memory capacity                 | 8 K words  |
| Logic execution time                 | 1.19 $\mu$ s   |
| Communication port(s)                | Serial RS-232C, Serial RS-485, USB                             |
| Number of Ethernet ports             | 0  |
| Number of USB ports                  | 1  |
| Number of RS-232 ports               | 1  |
| Number of RS-485 ports               | 1  |
| Communication option(s)              | CompoBus/S Slave, Serial RS-232C, Serial RS-422, Serial RS-485 |
| Max. encoder input frequency         | 100 kHz  |
| Max. number of PTP axes              | 0  |
| Max. pulse output frequency          | 0 kHz  |
| Function Block programming           | ✘  |
| Battery-free memory backup           | ✘  |
| Real-time clock                      | ✔  |
| Analogue option boards               | ✘  |
| Max. number of analogue I/O channels | 24   |