



سرج ارستر فونیکس کنتاكت

مدل 2 / SYS-SET



۰۲۱ ۶۶۷۵۶۲۳۱



www.alindas.com



خیابان سرهنگ سخایی ساختمان 44 طبقه سوم واحد 7



Technical data

Notes

Utilization restriction

EMC note

EMC: class A product, see manufacturer's declaration in the download area

Product properties

Product type

Feed-in module

Product family

MINI Analog Pro

Electrical properties

Maximum temperature coefficient

< 0.01 %/K

Input data

Input voltage range DC

9.9 V DC ... 30 V DC

Max. input current

3.2 A

Reverse polarity protection

yes

Output data

Output voltage range

9.6 V DC ... 29.7 V DC

Connection data

Input

Connection method

Push-in connection

Conductor cross section, rigid min.

0.14 mm²

Conductor cross section, rigid max.

2.5 mm²

Conductor cross section flexible min.

0.14 mm²

Conductor cross section flexible max.

2.5 mm²

Conductor cross section AWG min.

24

Conductor cross section AWG max.

12

Stripping length

10 mm

Interfaces

Interface

NFC interface

Signaling

Operating voltage display

Green LED (PWR 1)

Green LED (PWR 2)

Error indication

Red LED (ERR 1)

Red LED (ERR 2)